

Preparation unit——Lubricator



GL Series



GL

Symbol



Product feature

- 1. The structure of oil dripping adopts gap seal type, which makes the adjustment of oil supply more reliable.
- 2. Oil feed ring can only make one full turn. The quantity of oil supply basically takes on linear distribution. The quantity of oil supply can be generally calculated according to the position of graduation ring.
- 3. Special drip nozzle structure will produce negative pressure in oil dripping outlet and the mist flow is minimal.
- 4. Filling of oil while the lubricator is under pressure is made possible, and the oil bowl is large;
- 5. The bracket can be selected for installation.

Specification

Model	GL200-06	GL200-08	GL300-08	GL300-10	GL300-15	GL400-10	GL400-15	GL600-20	GL600-25
Fluid	Air								
Port size	1/8"	1/4"	1/4"	3/8"	1/2"	3/8"	1/2"	3/4"	1"
Pressure range	0.05~0.9MPa(7~130psi)								
Proof pressure	1.5MPa(215psi)								
Temperature range	-20~70℃								
Recommended lubricant	ISO VG 32 or equivalent								
Capacity of oil bowl	25CC		75CC		160CC		380CC		
Weight	130g		360g		670g		1300g		

Ordering code

GL200 08 ☐ P

Model

- GL200: G200 Series Lubricator
- GL300: G300 Series Lubricator
- GL400: G400 Series Lubricator
- GL600: G600 Series Lubricator

Thread type

- P: PT
- T: NPT
- G: G

Port size

- Model
- Port size
- GL200
 - 06: 1/8"
 - 08: 1/4"
- GL300
 - 08: 1/4"
 - 10: 3/8"
 - 15: 1/2"
- GL400
 - 10: 3/8"
 - 15: 1/2"
- GL600
 - 20: 3/4"
 - 25: 1"

Accessories

- Blank: Bracket
- J: No bracket(standard configuration)

Inner structure and Material of major parts

GL200

GL600

No.	Item	Material
1	Oil bowl	Aluminum alloy (GL600)\PC(others)
2	Adjusting spring	Stainless steel
3	O-ring	NBR
4	Body of lubricator	Aluminum alloy
5	Steel ball	Stainless steel
6	Distance block	TPU
7	O-ring	NBR
8	O-ring	NBR
9	Indicating ring	POM
10	Drip pipe	PC
11	Ejector pin	Brass
12	Screw	Carbon steel
13	Adjusting ring	POM
14	O-ring	NBR
15	Bowl	PC
16	Sprayer body	PA66
17	O-ring	NBR
18	O-ring	NBR
19	Sprayer bottom cap	POM
20	Liquid meter cover	SPCC
21	Liquid meter seal	NBR
22	Liquid meter inside cover	PC




Preparation unit—Lubricator




GL Series

Flow chart




Dimensions

GL200




GL300/GL400



Model/Item	A	B	C	D	E	F	G	H	I	J
GL300-08	41	1/4"	53.5	40	8	6.5	60	125	27	169
GL300-10	41	3/8"	53.5	40	8	6.5	60	125	27	169
GL300-15	41	1/2"	53.5	40	8	6.5	60	125	27	169
GL400-10	50	3/8"	71	55	11	8.5	80	142	33.5	190
GL400-15	50	1/2"	71	55	11	8.5	80	142	33.5	190

GL600



GL